

SATCO®

3 SERIES, 3 ROLLER, 24" PROCESSOR



Options available:

- Hardwood kit
- Alpine or thumbnail softwood rollers
- Measuring
 - **SATCO®** Plus 1
 - DASA5 PRIO
 - DASA5 Optimising
- Find end
- Colour marking
- Bottom delimb

Key features include:

- Twin tilt cylinders
- 360° continuous rotation
- Diameter 8cm (3") drive arm top, delimb and hanger pins for strength and long life
- Long life solenoids
- Rexroth valve rated at 420bar (6100psi) and 200lpm (52.8gpm) (US) continuous per section
- Reliable components
- All pivot pins are retained using **SATCO®**'s **'DEAD LOCK'** pin retention system, a special clip system adding to the strength of chassis with no extra weight
- The ability to customise from the build options to suit your needs
- Large 30cm (12") diameter length measuring wheel
- **SATCO®** Auto chain tensioner
- Standard safety chain shot zone lights
- Harvest Lock

Model	Topsaw SC150 Auto Saw Bar Tensioner	Roller Configuration	Main Saw Auto Saw Bar Tensioner
SAT324	Standard - 3/4"	MS11/OMV 630cc	3/4"




SATCO®

3 SERIES, 3 ROLLER, 24" PROCESSOR



SAT324	Processing Head	24"
Close Minimum:	7.5cm	3"
Open Maximum:	80cm	31"
Max Feed Speed:	"STANDARD" 5.8m/sec	19ft/sec
Rotation:	360° continuous rotation, heavy duty hydraulic centre joint system.	
Main Saw:	"STANDARD" Saw limiter SATCO® Auto chain tensioning 40" saw bar 3/4" chain Max cut - 78cm (31")	
Top Saw - SC150: Auto Tension	85cm (34") Bar - 3/4" Chain Max cut - 60cm (24")	
Feed Rollers:	Synchro drive x3	
Delimiting Knives:	3 upper, - all moving	
Measuring Wheel:	30cm diameter	12" diameter
Control Valve:	Rexroth M4-15	
Measuring:	- SATCO® Plus 1 - DASA5 PRIO - DASA5 Optimising	
Carrier Size:	24-33 tonne	
Weight:	3500kg	7700lbs
Optional:	- Bottom delimb - Paint marking - Find end	



SATCO®
LOGGING ATTACHMENTS

SATCO® Ltd | 6-14 Satco Drive, PO Box 254 | Tokoroa, New Zealand
p. +64 (7) 886 4539 | f. +64 (7) 886 4538 | e. admin@satco.co.nz | www.satco.co.nz

