SATCO

3 SERIES, 3 ROLLER, MEDIUM CAPACITY PROCESSORS













With one chassis option **SATCO*** can offer three different 3 Roller Processor configurations. Within those three different models there are further options to customise and refine your **SATCO*** 3 Series Processor to suit your application even further.

Further options within all three of the 'Basic Models' include:

- · Hardwood kit
- Alpine or thumbnail softwood rollers
- Measuring
 - SATCO® Plus 1
 - DASA5 PRIO
 - DASA5 Optimising
- · Find end
- Colour marking

Key features include:

- · Twin tilt cylinders
- 360° continuous rotation
- Diameter 8cm (3") drive arm pins for strength and long life
- Long life solenoids
- Rexroth valve rated at 420bar (6100psi) and 200lpm (52.8gpm) (US) continuous per section
- Reliable components
- All pivot pins are retained using SATCO*s 'DEAD LOCK' pin retention system, a special clip system adding to the strength of chassis with no extra weight
- The ability to customise from the build options to suit your needs
- Large 30cm (12") diameter length measuring wheel
- SATCO® Auto chain tensioner
- Standard safety chain shot zone lights
- Harvest Lock

The Models:

Models	Topsaw SC100	Roller Configuration	Main Saw Auto Saw Bar Tensioner
SAT318	Standard	TMTHW/OMV 500cc	3/4" or 404
SAT320	Standard	TMTHW/OMV 630cc	3/4" or 404
SAT323	Standard	MSII/OMV	3/4" or 404

SATCO

3 SERIES, 3 ROLLER, **MEDIUM CAPACITY PROCESSORS**



SAT323 SAT320	SAT318	Processing Head	Maria Tag
Close Minimum:		(5cm) 7.5cm	(2") 3"
Open Maximum:		80cm	31"
Max Feed Speed:	SAT323 SAT320 SAT318	"STANDARD" 5.8m/sec 5.8m/sec 7.4m/sec	19ft/sec 19ft/sec 24ft/sec
Rotation:		360° continuous rotation, heavy duty hydraulic centre joint system.	
Main Saw:		"STANDARD" SAT323 & SAT320 Saw limiter SATCO" Auto chain tensioning 40" saw bar 3/4" chain Max cut - 78cm (31")	
		"STANDARD" SATS Saw limiter SATCO* Auto chat404 or 3/4" chat36" saw bar Max cut - 64cm	in tensioning in
Top Saw - SC100:		26" bar - 404 chain, max cut 46cm (18")	
Feed Rollers:		Synchro drive x3	
Delimbing Knives:		3 upper, - all moving	
Measuring Wheel:		30cm diameter	12" diameter
Control Valve:		Rexroth M4-15	
Measuring:		- SATCO ° Plus 1 - DASA5 PRIO - DASA5 Optimising	
Carrier Size:		18-29 tonne	
Weight:	SAT323 SAT320 SAT318	2750kg 2650kg 2650kg	6050lb 5830lb 5830lb







